

# Mobile Generators Trailers & Skid-Mounted

- Robust rental-grade construction
- Heavy-duty, 4-cycle, EPA-certified Flex diesel engines
- Enlarged fuel cell for maximum run times
- Oversized alternator with PMG for superior starting
- Heavy gauge, powder-coated, lockable enclosure
- Dual-containment fuel cell and environmental containment basin
- Sound attenuation for superior noise reduction
- Voltage adjusting rheostat
- Emergency stop button
- Multi-voltage switch
- Lifting eye
- Deep Sea 7000-Series controllers
- Available with or without trailer
- 2-year/2000-hour warranty



Model	WSP12-1	WSP25	WSP40	WSP70	WSP80	WSP100	WSP125
<b>Standby Rating</b>	11.9 kW / 18.8 hp	27 kVA / 20 kW	38 kVA / 32 kW	69 kVA / 56 kW	83 kVA / 64 kW	101 kVA / 80 kW	123 kVA / 100 kW
<b>Prime Rating</b>	11.9 kW / 18.8 hp	25 kVA / 18 kW	35 kVA / 29 kW	63 kVA / 50 kW	75 kVA / 58 kW	93 kVA / 72 kW	112 kVA / 90 kW
<b>Voltages</b>	120/240	120/240 120/208 277/480	120/240 120/208 277/480	120/240 120/208 277/480	120/240 120/208 277/480	120/240 120/208 277/480	120/240 120/208 277/480
<b>Engine Model</b>	Perkins 403F-15G	Perkins 404D-22G	Perkins 404D-22TAG	Perkins 1104D-44TG1	Perkins 1104D-E44TG1	Perkins 1104D-E44TAG1/2	Perkins 1104D-E44TAG2
<b>Engine Type</b>	4-cycle indirect injection diesel	4-cycle indirect injection diesel	4-cycle indirect injection diesel	4-cycle direct injection turbo-charged diesel	4-cycle direct injection turbo-charged diesel	4-cycle direct injection turbo-charged diesel	4-cycle direct injection turbo-charged diesel
<b>Alternator</b>	Mecc Alte	Mecc Alte	Mecc Alte	Mecc Alte	Mecc Alte	Mecc Alte	Mecc Alte
<b>Emissions Certification*</b>	Tier 4 Final	Tier 4i Flex	Tier 4i Flex	Tier 3 Flex	Tier 3 Flex	Tier 3 Flex	Tier 3 Flex
<b>Fuel Tank Capacity</b>	60.7 gal (230 L)	60.7 gal (230 L)	60.7 gal (230 L)	124 gal (470 L)	124 gal (470 L)	158 gal (600 L)	177 gal (670 L)
<b>Continuous Run Time</b>							
<b>@ 25% load</b>	291.0 hr	101.2 hr	55.2 hr	88.6 hr	51.7 hr	56.4 hr	47.8 hr
<b>@ 50% load</b>	83.1 hr	60.7 hr	46.7 hr	53.9 hr	38.8 hr	45.1 hr	42.1 hr
<b>@ 75% load</b>	58.2 hr	50.6 hr	22.5 hr	36.5 hr	27.6 hr	32.2 hr	30.5 hr
<b>@ 100% load</b>	48.5 hr	38.0 hr	25.3 hr	25.3 hr	24.3 hr	25.5 hr	23.3 hr
<b>Standby Current</b>							
<b>@ 120/240V, 1-phase</b>	25 A	54 A	88 A	154 A	175 A	217 A	275 A
<b>@ 120/240V, 3-phase</b>	—	60 A	96 A	168 A	192 A	241 A	301 A
<b>@ 120/208V, 3-phase</b>	—	69 A	111 A	195 A	222 A	278 A	347 A
<b>@ 277/480V, 3-phase</b>	—	30 A	48 A	84 A	96 A	120 A	150 A
<b>Sound Level @ 23ft (7m)</b>	59 dBA	59 dBA	59 dBA	69 dBA	69 dBA	69 dBA	69 dBA
<b>Dimensions, L x W x H</b>	77 x 32 x 49 in (195 x 80 x 125 cm)	90 x 42 x 62 in (229 x 107 x 158 cm)	90 x 42 x 62 in (229 x 107 x 158 cm)	112 x 44 x 70 in (284 x 112 x 178 cm)	112 x 44 x 70 in (284 x 112 x 178 cm)	120 x 44 x 77 in (304 x 112 x 196 cm)	120 x 44 x 77 in (304 x 110 x 196 cm)
<b>Dry Weight</b>	2020 lb (918 kg)	2920 lb (1324 kg)	4025 lb (1826 kg)	4400 lb (1996 kg)	4620 lb (1996 kg)	4840 lb (2195 kg)	5060 lb (2295 kg)
<b>Dimensions with Trailer, L x W x H</b>	155 x 55 x 73 in (393 x 139 x 186 cm)	154 x 71 x 79 in (391 x 180 x 201 cm)	154 x 71 x 79 in (391 x 180 x 201 cm)	186 x 77 x 87 in (472 x 196 x 221 cm)	186 x 77 x 87 in (472 x 196 x 221 cm)	186 x 77 x 94 in (472 x 196 x 239 cm)	186 x 77 x 94 in (472 x 196 x 239 cm)
<b>Dry Weight with Trailer</b>	2440 lb (1107 kg)	3900 lb (1769 kg)	5000 lb (2268 kg)	5350 lb (2427 kg)	5350 lb (2427 kg)	5570 lb (2527 kg)	5790 lb (2626 kg)

Trailers include all-welded structural steel frame, with electric brakes (optional on some models), running lights, license plate bracket and ball or pintle hitch.

\*Tier 3 Flex and Tier 4i Flex engines are subject to availability. For Tier 4 Final engine availability, contact factory.



**WANCO INC.**  
5870 Tennyson Street  
Arvada, Colorado 80003  
800-972-0755  
303-427-5700  
303-427-5725 fax  
[www.wanco.com](http://www.wanco.com)

Due to Wanco's commitment to continuous improvement of our products, all information is subject to change without notice. Wanco and the Wanco logo are registered trademarks of Wanco Inc. All other trademarks are property of their respective owners.

©2018 Wanco Inc. All rights reserved. Printed in the USA. | WPB0067 March 2018

Printed on recycled paper