

PTO GENERATORS – 3600RPM

		
	PTO15/12	PTO30/25M
Voltage	120/240 Vac	120/240 Vac
Max. output	15,000 W	30,000 W
Rated output	12,000 W	25,000 W
Rated current	100 A @ 120 V 50 A @ 240 V	208 A @ 120 V 104 A @ 240 V
Frequency	60 Hz	60 Hz
Generator RPM	3600	3600
Tractor PTO RPM	540	540
Generator shaft	1 $\frac{3}{8}$ in 6-spline	1 $\frac{3}{8}$ in 6-spline
Required PTO power	25 hp	50 hp
Max. motor starting code G	7.5	10
Receptacles	One 120Vac 20A duplex One 240Vac 30A locking One 240Vac 50A straight-blade	One 120Vac 20A duplex One 240Vac 30A locking One 240Vac full-power connector
Dimensions, L x W x H	29 x 11 x 16 in (74 x 28 x 41 cm)	29 x 13 $\frac{3}{4}$ x 21 in (74 x 35 x 53 cm)
Dry weight, approx.	159 lb (72 kg)	303 lb (137 kg)
Optional accessories	Drive shaft, 37–50 in (94–127 cm) Drive shaft, 64–79 in (163–200 cm) 2-wheel trailer 3-point hitch platform	Drive shaft, 37–50 in (94–127 cm) Drive shaft, 64–79 in (163–200 cm) 2-wheel trailer 3-point hitch platform
<p>Deratings: Ratings apply for altitudes from sea level up to 1,000 feet (305 meters) with typical cooling, normal ambient temperature and gasoline fuel. Reduce ratings 3.5% for each 1000 feet (305 meters) above sea level and 1.0% for each 10°F rise above 60°F (5.6°C above 15.6°C).</p>		